

---

Subject: Whitelist - how?

Posted by [Mark Haller](#) on Tue, 10 Aug 2004 17:34:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I'm going to make a fool of myself, so please excuse me in advance.

How do I setup the whitelist functions? I want to write an interface back from our mail application (Lotus Notes) ... to add a whitelist entry.

But ... excuse me ... I've looked through the very simple html files provided as some kind of support and they expect you to have a much better understanding than myself.

Any pointers would be greatly appreciated.

Mark Haller  
LogicSpot  
UK

---

---

Subject: Re: Whitelist - how?

Posted by [support](#) on Fri, 13 Aug 2004 07:28:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

> How do I setup the whitelist functions? I want to write an  
> interface back from our mail application (Lotus Notes) ... to  
> add a whitelist entry.

Let this interface write a small text file in the "sa\ruleset" subdirectory of your installation. If this file has the extension ".cf" SpamAssassin will pick it up automatically on each run, so "local\_whitelist.cf" would be suitable.

For each sender address you want to whitelist, add a line like this:

```
whitelist_from      some_address@somedomain.org
```

Separate the keyword "whitelist\_from" from the entry with white space (blanks or tabs).

> But ... excuse me ... I've looked through the very simple  
> html files provided as some kind of support and they expect you  
> to have a much better understanding than myself.

Most of the interesting SpamAssassin configuration info is in this HTML document:

[Mail\\_SpamAssassin\\_Conf.htm](#)

If you are not sure if your new rules and settings actually work, you can run a syntax check, as described in this FAQ entry:

